



MATERIAL SAFETY DATA SHEET

Page 1 of 5

BK021 - BAKOR AIR BLOC 21

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 05/20/2011 Product Name: BK021 - BAKOR AIR BLOC 21 Product Code: BK021 Product/Material Uses Air barrier insulation adhesive	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
bentonite	1302-78-9		1 - 5
calcium carbonate	1317-65-3		30 - 50
hydrocarbon resin	68132-00-3		10 - 20
mineral oil - poorly refined	64742-65-0		1 - 5
light aliphatic naphtha	64742-49-0		10 - 30
silica, quartz	14808-60-7		0.1 - 1

EMERGENCY OVERVIEW	
WARNING! Flammable liquid and vapor. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Central nervous system depressant. Causes severe eye irritation. Skin and respiratory system irritant.	
Appearance/Odor: Cream colored paste with hydrocarbon odor.	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause severe eye irritation (burning, tearing, redness or swelling) and blurred vision.
Skin Hazards May cause moderate skin irritation, defatting, and contact dermatitis upon prolonged contact.



BK021 - BAKOR AIR BLOC 21

<p>3. Hazards Identification - Continued</p> <p><u>Ingestion Hazards</u> May cause gastric distress, vomiting and diarrhea</p> <p><u>Inhalation Hazards</u> Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.</p> <p><u>Chronic/Carcinogenicity Effects</u> This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.</p>
<p>4. First Aid Measures</p> <p><u>Eye</u> In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.</p> <p><u>Skin</u> Remove contaminated clothing and shoes. Wash affected areas with soap and water.</p> <p><u>Ingestion</u> Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.</p> <p><u>Inhalation</u> Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.</p>
<p>5. Fire Fighting Measures</p> <p>Flash Point: 19.4 °F -7 °C Flash Point Method: closed cup Autoignition Point: 446-626 °F 230-330 °C Flammability Class: Flammable Lower Explosive Limit: 1.0 Upper Explosive Limit: 7.0</p> <p><u>Fire And Explosion Hazards</u> Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes, including traces of 1-3 butadiene, styrene monomer, sulfur dioxide (SO₂) and carbon monoxide (CO).</p> <p><u>Extinguishing Media</u> Chemical foam, carbon dioxide (CO₂), or dry chemical, or water spray.</p> <p><u>Fire Fighting Instructions</u> Firefighters should wear self-contained breathing apparatus and full protective gear. Water can be used to cool and protect exposed material. Vapors may form explosive mixtures.</p>
<p>6. Accidental Release Measures</p> <p>Ventilate area. Avoid open flames, sparks or other ignition sources. Contain any liquids and absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations.</p>
<p>7. Handling And Storage</p> <p><u>Handling And Storage Precautions</u> Store in a cool, dry, well-ventilated area. Keep away from ignition sources. Keep containers tightly closed.</p>

BK021 - BAKOR AIR BLOC 21

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with solvent-resistant rubber gloves, protective sleeves and solvent-resistant apron to prevent skin contact.

Respiratory Protection

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

bentonite

ACGIH TLV-TWA 10 mg/m³ (total dust)

ACGIH TLV-TWA 3 mg/m³ (respirable dust)

OSHA PEL-TWA 15 mg/m³ (total dust)

OSHA PEL-TWA 5 mg/m³ (respirable dust)

mineral oil - poorly refined

ACGIH TLV-TWA 5mg/m³

silica, quartz

ACGIH TLV-TWA 0.025 mg/m³

OSHA PEL-TWA 30mg/m³ / (%SiO₂+2) (total dust)

OSHA PEL-TWA 10 mg/m³/ (%SiO₂+2) (respirable dust)

9. Physical And Chemical Properties

Appearance

Cream-colored paste

Odor

Hydrocarbon odor

Chemical Type: Mixture

Physical State: Liquid

Boiling Point: 194 °F 90 °C

Specific Gravity: 1.23-1.25

Percent Volatiles: 25-29 %

Vapor Pressure: 0-80 at 38°C

Vapor Density: 2.5-4.8

pH Factor: not applicable

Solubility: insoluble

Evaporation Rate: 3.5 (Butyl Acetate = 1)

10. Stability And Reactivity

Stability: stable

Hazardous Polymerization: not expected to occur

BK021 - BAKOR AIR BLOC 21

<p>10. Stability And Reactivity - Continued</p> <p><u>Conditions To Avoid (Stability)</u> Avoid extreme temperatures. Keep away from ignition sources, heat and flames.</p> <p><u>Incompatible Materials</u> Avoid contact with strong oxidizing agents.</p> <p><u>Hazardous Decomposition Products</u> Decomposition will not occur if handled and stored properly.</p>
<p>11. Toxicological Information</p> <p><u>Chronic/Carcinogenicity</u> Silica, quartz present in this product, at concentrations equal to or greater than 0.1%, has been determined to be carcinogenic as follows: IARC: Group 1, NTP:listed, OSHA: not regulated, or ACGIH: A2.</p> <p><u>Miscellaneous Toxicological Information</u> Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.</p> <p><u>Ingredient(s) - Carcinogenicity</u> silica, quartz NTP - Listed On The National Toxicology Program Listed In The IARC Monographs</p> <p><u>Ingredient(s) - Toxicological Data</u> calcium carbonate LD50 (oral-rat) : 6450 mg/kg mineral oil - poorly refined IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): Mineral Oil - Poorly Refined. ACGIH has designated the following chemicals in this product as a suspected human carcinogen (A2): Mineral Oil - Poorly Refined. silica, quartz LD50 (iv-rat) : 500 mg/kg bw/Quartz (10-200 um)</p>
<p>12. Ecological Information</p> <p>None identified.</p>
<p>13. Disposal Considerations</p> <p>Do not allow into any sewer, on the ground, or into any body of water. Dispose in accordance with applicable federal, state and local government regulations.</p>
<p>14. Transport Information</p> <p>Ground UN1133, Adhesives, 3, II</p> <p>IMDG UN1133, Adhesives, 3, II</p> <p>IATA UN1133, Adhesives, 3, II</p>

BK021 - BAKOR AIR BLOC 21

DOT (Pictograms)



15. Regulatory Information

Ingredient(s) - State Regulations

calcium carbonate
 Pennsylvania - Workplace Hazard
 silica, quartz
 New Jersey - Workplace Hazard
 Pennsylvania - Workplace Hazard
 California - Proposition 65
 Massachusetts - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: Class B3 - Combustible or Flammable Material, D2A - Very Toxic


Ingredient(s) - Canadian Regulatory Information

silica, quartz
 WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 10/10/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).